

## Utensili da traccia

Marking tools

Pointes à tracer



0296/1  
0296/2  
0296/3

### Compasso "Extra" di precisione a molla con vite di apertura rapida

"Extra" precision spring caliper with quick opening screw

Compas "Extra" de précision à ressort avec vis d'ouverture rapide

**apertura** / opening / ouverture: max 70 mm - **gambi** / legs / branches: 75 mm

**apertura** / opening / ouverture: max 90 mm - **gambi** / legs / branches: 100 mm

**apertura** / opening / ouverture: max 200 mm - **gambi** / legs / branches: 200 mm



0297/1  
0297/2

### Compasso "Standard" di precisione a molla con vite di apertura normale

"Standard" precision spring caliper with quick opening screw

Compas "Standard" de précision à ressort avec vis d'ouverture normale

**apertura** / opening / ouverture: max 72 mm - **gambi** / legs / branches: 75 mm

**apertura** / opening / ouverture: max 95 mm - **gambi** / legs / branches: 100 mm



0298/1  
0298/2

### Compasso da segno

Slim-legs dividers

Compas à pointes aiguées

**apertura** / opening / ouverture: max ca. 210 mm - **gambi** / legs / branches: 150 mm

**apertura** / opening / ouverture: max ca. 300 mm - **gambi** / legs / branches: 200 mm



0299/1  
0299/2

### Compasso da segno con corsoio ad arco

Slim-legs dividers with curved slider

Compas à pointes avec coulisseau à arc

**apertura** / opening / ouverture: max 225 mm - **gambi** / legs / branches: 150 mm

**apertura** / opening / ouverture: max 275 mm - **gambi** / legs / branches: 200 mm



0717/1

### Punta da segno "SW" (2 punte diritte), L = 180 mm

"SW" marking point (2 straight points), L = 180 mm

Pointe à tracer "SW" (2 pointes droites), L = 180 mm

0717/3

### Punta da segno "SW" (1 punta diritta, 1 punta curva), L = 165 mm

"SW" marking point (1 straight point, 1 curved point), L = 165 mm

Pointe à tracer "SW" (1 pointe droite, 1 pointe courbée), L = 165 mm



0717/2

### Punta da segno "Dick" (1 punta diritta, 1 punta brunitore), L = 180 mm

"Dick" marking points (1 straight point, 1 burnisher point), L = 180 mm

Pointe à tracer "Dick" (1 pointe droite, 1 pointe brunissoir), L = 180 mm



0823/01

### Bulino automatico a battuta regolabile

Automatic point chisel with adjustable pressure

Pointeau automatique à force de frappe réglable

0823/03

**Punta di ricambio** / Spare bit / Pointe de rechange

## Utensili da traccia e misura

Marking and measuring tools

Outils à tracé et mesurer



**0293A**

**Truschino con scala millimetrata (200 mm) e cursore mobile**

Surface gauge with millimetre scale (200 mm) and mobile cursor

Trusquin avec échelle millimétrée (200 mm) et curseur mobile



**Squadra di precisione (90°),rettificata in acciaio temperato**

Precision square (90°), ground in tempered steel

Equerre de précision (90°), rectifiée en acier trempé

**0305/2**

**100 x 75 mm**

**0305C/2**

**100 x 75 mm - con base / à chapeau / with foot**

**0305/4**

**150 x 100 mm**

**0305/5**

**200 x 130 mm**

**0305/6**

**250 x 100 mm**

**0305/7**

**300 x 200 mm**



**Righelli in acciaio flessibile**

Flexible steel rulers / Règlettes en acier flexible

**0292/1**

**200 mm = scala / scale / échelle**

**0292/2**

**250 mm = scala / scale / échelle**

**0292/3**

**300 mm = scala / scale / échelle**

**0292/4**

**500 mm = scala / scale / échelle**

**0293/3**

**300 mm / 12" = scala / scale / échelle**

**0293/4**

**500 mm / 20" = scala / scale / échelle**